

REMARKS


Original claims 1-10 have been canceled. New claims 11-18 have been added in this application to clarify the subject matter of the invention as compared to the original, canceled claims.

The application and abstract have been amended to correct various typographical, grammatical and idiomatic informalities, and to place the application into proper conformance with U.S. patent practice.


In light of the foregoing, it is respectfully submitted that the application is in proper form for allowance of all claims and notice to that effect is earnestly solicited.

Respectfully submitted,

Jordan and Hamburg LLP

By 
C. Bruce Hamburg
Reg. No. 22,389
Attorney for Applicants

and,

By 
T. David Bomzer
Reg. No. 48,770
Attorney for Applicants

122 East 42nd Street
New York, New York 10168
(212) 986-2340

SPECIFICATION**CLAMP DEVICE****FIELD BACKGROUND OF THE INVENTION**

The present invention relates to a clamp device for clamping an object to
5 ~~be clamped~~, such as a workpiece, to a ~~fixing base such as a~~ fixture base, a
machine table or the like.

BACKGROUND ART

Conventionally, there has been a clamp device 511, as shown in FIG.
17, for clamping an object ~~to be clamped~~, such as a workpiece, to a ~~fixing base~~
10 ~~such as~~ a fixture base, an MC pallet, a machine table or the like.- The clamp
device 511 includes: a body 512 that is attached to a ~~fixing~~support base 501; a
pressing member 513 for ~~pressing to clamp~~clamping the workpiece 502; a
tightening bolt 514; and a coil spring 515.- The body 512 has a shank portion
512a that is formed with a thread hole 512b. ~~Besides~~In addition, the pressing
15 member 513 is attached to the shank portion 512a so as to rotate and slide
axially.- The pressing member 513 is formed with a claw portion 513a
projecting sideways to press the workpiece 502. -The tightening bolt 514 passes
~~through~~through the pressing member 513 and engages the thread hole 512b
formed in the body 512.- As the tightening bolt 514 is tightened into the thread
20 hole 512b, the pressing member 513 slides axially, causing the claw portion

MARKED SPECIFICATION

F-8660

Ser. No.

513a to press the workpiece 502. -Thus the workpiece 502 is fixed to the fixingsupport base 501.

5 In the conventional clamp device 511 as described above, the workpiece 502 is clamped as follows: first, in the state in which the claw portion 513a of the pressing member 513 is rotated to a position not facing the workpiece 502, the workpiece 502 is placed on the fixingsupport base 501; then the pressing member 513 is rotated so that the claw portion 513a faces the workpiece 502. After that, the tightening bolt 514 is tightened until the workpiece 502 is clamped to the fixingsupport base 501.- If the workpiece 502 is to be removed, 10 first the tightening bolt 514 is loosened.- After that, the pressing member 513 is rotated until the claw portion 513a of the pressing member 513 does not face the workpiece 502. -Then the workpiece 502 can be removed from the fixingsupport base 501.- In this way, the conventional clamp device 511, if the workpiece 502 is clamped to or removed from the fixingsupport base 501, 15 requires two different kinds of work, that is, one work of rotating the pressing member 513 and the other work of tightening up or loosening the tightening bolt 514, which is very cumbersome.

 The present invention has been made to overcome the conventional drawbacks described above.- The object of the invention is to provide a clamp

device that enables easier attachment and removal of an object to be clamped to and from a fixingsupport base.

DISCLOSUREBRIEF SUMMARY OF THE INVENTION

To achieve the above object a clamp device according to the present invention is constituted as follows.

That is to say, the clamp device according to the invention is a clamp device which clamps an object to ~~be clamped to a~~ fixingsupport base and comprises: a body detachably secured to the fixingsupport base, a pressing member for ~~pressing to clamp~~ clamping the object, and a rotary member ~~to be operated for rotation.~~ Here, the body, the pressing member, and the rotary member are combined so as to rotate relative to each other about an axis. -The pressing member is ~~adapted to rotate~~ rotates between a first rotary position not axially facing the object ~~in the same direction as the axial direction~~ and a second rotary position axially facing the object ~~in the same direction as the axial direction.~~ - The rotary member is ~~adapted to rotate~~ rotates between one rotary position on the ~~side of the first rotary position~~ side and ~~the other~~ another rotary position past a middle rotary position on the ~~side of the second rotary position~~ side. - The pressing member is ~~adapted to move in the same direction as the axial direction~~ axially translates between a press releasing position on a press releasing side and a pressing position on a pressing side so as to press the object

MARKED SPECIFICATION

F-8660

Ser. No.

and release the press in the second rotary position. -Here, the clamp device has:
a contact means, a holding means, a rotary range restricting means, and an
interlock means.- The contact means forces the pressing member and the rotary
member to contact with each other so that the pressing member rotates between
5 the first rotary position and the second rotary position as the rotary member
rotates. -The holding means ~~is adapted to hold~~holds the pressing member in the
press releasing position between the first rotary position and the second rotary
position. -The rotary range restricting means ~~is adapted to prevent~~prevents the
pressing member from rotating from the second rotary position to a side
10 opposite the first rotary position. -The interlock means ~~is adapted to move~~moves
the pressing member in the second rotary position, between the press releasing
position and the pressing position, ~~as interlocked~~and interlocks with the rotation
of the rotary member between the middle rotary position and the other rotary
position.

15 _ When the rotary member is rotated from the one rotary position to the
middle rotary position, the pressing member, while being held in the press
releasing position by the holding means, is rotated by the contact means from
the first rotary position to the second rotary position as the rotary member
rotates. -When the rotary member is rotated from the middle rotary position to
20 the other rotary position, the pressing member, while ~~being remained~~remaining

MARKED SPECIFICATION

F-8660

Ser. No.

in the second rotary position by the rotary range restricting means, is moved by the interlock means from the press releasing position to the pressing position and presses the object.- When the rotary member is rotated from the other rotary position to the one rotary position side, the pressing member is moved by the interlock means from the pressing position to the press releasing position side, and is rotated by the contact means from the second rotary position to the first rotary position as the rotary member rotates.

— In this way, if the object is to be clamped to the fixingsupport base using the clamp device, the object is placed in the clamping position followed by rotating the rotary member from the one rotary position to the other rotary position past the middle rotary position. -In such a way, the pressing member is rotated from the first rotary position not facing the object to the second rotary position facing the object, as the rotary member rotates up to the middle rotary position. -By rotating the rotary member to the other rotary position, the pressing member, while ~~being remained~~remaining in the second rotary position, moves from the press releasing position ~~on the press releasing side~~ to the pressing position ~~on the pressing side~~, to press the object.- In this way, the object is clamped to the fixingsupport base.—

_____ In contrast, if the object is to be removed from the fixingsupport base, the rotary member is rotated from the other rotary position to the one rotary

MARKED SPECIFICATION

F-8660

Ser. No.

position.- This causes the pressing member to move from the pressing position to the press releasing position side, and rotates from the second rotary position facing the object to the first rotary position not facing the object, resulting in the removal of the object from the fixingsupport base.- In other words, by use of
5 this clamp device, when the object to be clamped is placed on and clamped to the fixingsupport base or the object is removed from the fixingsupport base, the pressing member is rotated between the first rotary position not facing the object and the second rotary position facing the object by rotating the rotary member. -Then the pressing member is moved between the press releasing
10 position ~~on the press releasing side~~ and the pressing position ~~on the pressing side~~.- It is therefore easy to clamp the object to the fixingsupport base and remove it therefrom.

- In the clamp device according to the invention, the body of the clamp device is provided with an axial bore ~~extending along the axis~~, the rotary
15 member has a shank portion that is rotatably inserted in the axial bore, and the rotary member ~~is adapted to rotate~~ rotates relative to the body about the axis.- The pressing member has a through-hole for the shank portion to pass and is allowed to rotate about the axis relative to the rotary member.- In other words, in the clamp device, the shank portion of the rotary member passes through the
20 axial bore formed in the body and also through the through-hole formed in the

MARKED SPECIFICATION

F-8660

Ser. No.

pressing member, so that the body, the pressing member, and the rotary member are allowed to rotate relative to each other about the axis.

- Also, the rotary range restricting means includes: a projection disposed in ~~either~~ one of the body and the pressing member; and a recess such as a hole or a cut out formed in the other of the body and the pressing member, to receive the projection and allow the projection to move. ~~Here, when the pressing member rotates from the first rotary position to the second rotary position, the projection relatively moves~~moves relative to and within the recess and comes into contact with the inside surface thereof, resulting in prevention of further movement of the projection.

- The holding means includes a resilient body for urging the pressing member toward the press releasing position from the pressing position. ~~In this way, the pressing member is urged by the resilient body toward the press releasing position on the press releasing side from the pressing position on the pressing side~~ and held in the press releasing position between the first rotary position and the second rotary position.

- The interlock means comprises: a guide means for axially guiding the rotary member ~~to move in the same direction as the axial direction by the rotation of the rotary member~~as it rotates, and a support means for supporting the pressing member so that it moves between the press releasing position and

MARKED SPECIFICATION

F-8660

Ser. No.

the pressing position as the rotary member ~~moves in the same direction as the axial direction~~axially translates. - Owing to the rotation of the rotary member between the middle rotary position and the other rotary position, the rotary member is guided to ~~move in the same direction as the axial direction~~axially translate. - Along with this movement, the pressing member supported by the support means moves between the press releasing position ~~on the press releasing side~~ and the pressing position ~~on the pressing side~~.

- The guide means includes: a guided projection disposed in ~~either~~ one of the body and the rotary member; and a guide surface provided in the other of the body and the rotary member, for ~~relatively~~ guiding the guided projection relative to the guide surface. - In this way, as the guided projection is ~~relatively guided~~guided relative to and with the guide surface, the rotary member is guided to ~~move in the same direction as the axial direction~~axially translate.

- The support means includes: a resilient element for urging the pressing member toward the press releasing position from the pressing position, and a receiving portion disposed in the rotary member for receiving the pressing member against the urging force of the resilient element. -Therefore, when the rotary member, ~~when it~~ rotates between the middle rotary position and the other rotary position and is guided by the guide means ~~to move in the same direction as the axial direction~~to axially translate, along with this movement, the pressing

MARKED SPECIFICATION

F-8660

Ser. No.

member urged by the resilient element ~~and, is~~ received on the receiving portion of the rotary ~~member moves member and is translated~~ between the press releasing position and the pressing position ~~along with the movement in the same direction as the axial direction.~~

5 _ The contact means includes a resilient member for urging a first sliding surface and a second sliding surface of the pressing member and the rotary member facing each other to come into tight contact with each other. - In this way, as the first sliding surface and the second sliding surface of the pressing member and the rotary member facing each other are urged by the resilient
10 member to come into tight contact with each other, the pressing member securely rotates between the first rotary position and the second rotary position as the rotary member rotates.

 _ The contact means comprises: ~~in addition to~~ the resilient member, an engagement recess provided on one of the pressing member and the rotary
15 member; and an engagement member that is provided in the other of the pressing member and the rotary member and has an engagement portion resiliently urged to releasably engage the engagement recess. -Engagement of the resiliently urged engagement portion with the engagement recess as described above makes it possible to stop relative rotation of the pressing
20 member and the rotary member, so that the pressing member rotates more

MARKED SPECIFICATION

F-8660

Ser. No.

securely between the first rotary position and the second rotary position as the rotary member rotates.

5 The pressing member is guided, while being located in the press releasing position, to move from a side distant from the pressing position to a side near the pressing position as the pressing member rotates from the first rotary position to the second rotary position.- In this way, with the press releasing position having a range, when the pressing member rotates from the first rotary position to the second rotary position, the pressing member moves from the side distant from the pressing position to the side near the pressing position.-

10 Therefore, even if any obstacle is present on the way the pressing member moves from the first rotary position to the second rotary position, the pressing member can pass the obstacle.- Moreover, because the pressing member approaches the pressing position while it rotates from the first rotary position to the second rotary position, it is possible to reduce the stroke defined between the press releasing position and the pressing position in the second rotary position.- Therefore, it is possible to increase the force of the pressing member for pressing the object.

BRIEF DESCRIPTION OF DRAWINGS

Accompanying the specification are figures which assist in illustrating the embodiments of the invention, in which:

- FIG. 1 is an exploded, perspective view of a clamp device of an embodiment according to the invention;

- FIG. 2 is a plan view, in which a rotary member is in one rotary position, and a pressing member is in a first rotary position and in a press releasing position;

- FIG. 3 is a cross sectional view, taken along a line A-A, in FIG 2;

- FIG. 4 is a plan view, in which the rotary member is in a middle rotary position, and the pressing member is in a second rotary position and in the press releasing position;

- FIG. 5 is a cross sectional view, taken along a line B-B, in FIG. 4;

- FIG. 6 is a plan view, in which the rotary member is in ~~the other~~another rotary position, and the pressing member is in the second rotary position and in the pressing position;

- FIG. 7 is a cross sectional view, taken along a line C-C, in FIG. 6;

- FIG. 8 is a plan view, in which the rotary member is in the other rotary position and in the maximum rotary position, and the pressing member is in the second rotary position and in the maximum pressing position;

MARKED SPECIFICATION

F-8660

Ser. No.

- FIG. 9 is a cross sectional view, taken along a line D-D, in FIG. 8;

- FIG. 10 is a perspective view, showing a state in use with a workpiece yet to be attached or removed;

- FIG. 11 is a perspective view, showing a state in use with a workpiece attached;

- FIG. 12 is a cross sectional view, showing a first modification of the embodiment of the clamp device according to the invention;

- FIG. 13 is a perspective view, showing a second modification of the embodiment of the clamp device according to the invention;

10 - FIG. 14 is a plan view, showing a third modification of the embodiment of the clamp device according to the invention;

- FIG. 15 is a cross sectional view, taken along a line E-E, in FIG. 14;

- FIG. 16 is a cross sectional view, showing a fourth modification of the embodiment of the clamp device according to the invention; and

15 - FIG. 17 is a cross sectional view, showing a conventional clamp device.

BEST MODE DETAILED DESCRIPTION OF EMBODYING THE

INVENTION

- Clamp devices embodied according to the invention are described below, with reference to the accompanying drawings.

MARKED SPECIFICATION

F-8660

Ser. No.

FIGs. 1 to 11 show a clamp device as an embodiment of the invention.

~~In the drawings~~Referring to FIG. 3, reference numeral 1 denotes a ~~fixingsupport~~ base, such as a fixture base, that is attached to a machine table or a pallet of a machine tool such as a machining center. -Reference numeral 2 represents for example a workpiece, an object to be clamped, as an object to be processed. -Reference numeral 3 represents a clamp device for clamping the workpiece 2 to the ~~fixingsupport~~ base 1.

The clamp device 3 includes: a body 4 removably attached to the ~~fixingsupport~~ base 1; a pressing member 5 for ~~pressing to clamp~~clamping the workpiece 2; and a rotary member 6 ~~operated for rotation~~. - The body 4, the pressing member 5, and the rotary member 6 are combined so as to ~~relatively rotate~~rotate relative to each other about an axis 7.- Thus, the pressing member 5 is allowed to rotate between a first rotary position (See FIGs. 2 and 3) not axially facing the workpiece 2 ~~in the same direction as of the axis 7~~ and a second rotary position (See FIGs. 4 and 5) axially facing the workpiece 2 ~~in the same direction as of the axis 7~~. - The rotary member 6 is allowed to rotate between one rotary position (See FIG. 2) on the first rotary position side and ~~the other~~another rotary position (See FIGs. 6 and 8) past a middle rotary position (See FIG. 4) on the second rotary position side. ~~In the illustrated embodiment, the~~The body 4 has an axial bore 4a therethrough ~~in the direction~~

MARKED SPECIFICATION

F-8660

Ser. No.

~~of the axis 7.~~ - On the other hand, the rotary member 6 has a shank portion 6a that is rotatably inserted in the axial bore 4a of the body 4, so that the rotary member 6 may axially ~~rotate about the axis 7~~ relative to the body 4. - The pressing member 5 has a through-hole 5a to permit the shank portion 6a of the rotary member 6 to pass, so that the pressing member 5 may axially ~~rotate about the axis 7~~ relative to the rotary member 6. - Thus, as for this clamp device 3, the body 4, the pressing member 5, and the rotary member 6 are allowed to ~~rotate relatively about the axis 7 since~~ relative axial rotation because the shank portion 6a of the rotary member 6 is inserted in the axial bore 4a of the body 4 and the through-hole 5a of the pressing member 5.

- The pressing member 5 ~~is adapted to move~~ axially translates between a press releasing position (See FIG. 5) on a press releasing side and a pressing position (See FIGs. 7 and 9) on a pressing side ~~in the same direction as of the axis 7~~ so that it presses the workpiece 2 and releases the press in the second rotary position.

- Here, the clamp device 3 includes a contact means 110, a holding means 120, a rotary range restricting means 130, and an interlock means 140.

- The contact means 110 ~~serves to cause~~ causes the pressing member 5 and the rotary member 6 to contact ~~with~~ each other so that the pressing member 5 rotates between the first rotary position (See FIGs. 2 and 3) and the second

MARKED SPECIFICATION

F-8660

Ser. No.

rotary position (See FIGs. 4 and 5) as the rotary member 6 rotates.

Specifically, the contact means 110 includes a coil spring 8 as a resilient member for urging ~~the~~a first sliding surface 5b and ~~the~~a second sliding surface 6b of the pressing member 5 and the rotary member 6 facing each other to

5 contact closely each other. -More specifically, the contact means 110 has:~~in addition to~~ the coil spring 8 serving as a resilient member, an engagement recess 111 disposed in one of the pressing member 5 and the rotary member 6; and an engagement member 113 which is disposed in the other of the pressing member 5 and the rotary member 6 and has an engagement portion 112

10 resiliently urged to releasably engage the engagement recess 111. ~~In the illustrated embodiment, the~~The engagement recess 111 is formed in the pressing member 5, while the engagement member 113 is formed in the rotary member 6. -The engagement member 113 is a plunger 9 that is attached to, ~~as~~and embedded in, the rotary member 6.- The engagement portion 112 is a pressing
15 piece 9a such as a ball, which is placed at the tip of the plunger 9. -The pressing piece 9a is resiliently urged by a spring 9b disposed in the plunger 9.

- The holding means 120 ~~serves to hold~~holds the pressing member 5 in the press releasing position between the first rotary position (See FIGs. 2 and 3) and the second rotary position (See FIGs. 4 and 5).- Specifically, the holding
20 means 120 includes the coil spring 8 as a resilient body for urging the pressing

MARKED SPECIFICATION

F-8660

Ser. No.

member 5 toward the press releasing position from the pressing position. - Thus, the pressing member 5 is urged by the coil spring 8 as a resilient body toward the press releasing position on the press releasing side from the pressing position on the pressing side and held in the press releasing position between the first rotary position and the second rotary position. -More specifically, the coil spring 8 is interposed between the body 4 and the pressing member 5 so as to urge the pressing member 5.- The coil spring 8 urges the pressing member 5 not directly but indirectly through an outer cylinder 10 which will be described later. -As described above, while the pressing member 5 is urged by the coil spring 8 ~~as a resilient body~~, the urging force, ~~in the illustrated embodiment~~, is received by a receiving portion 6c of the rotary member 6, to be described later, and the pressing member 5 is held in the press releasing position.

The rotary range restricting means 130 ~~serves to prevent~~prevents the pressing member 5 from rotating from the second rotary position to the side opposite the first rotary position. -Specifically, the rotary range restricting means 130 includes a projection 131 disposed in ~~either~~ one of the body 4 and the pressing member 5, and a recess 132 such as a hole or a cut out, which is provided in the other of the body 4 and the pressing member 5 and receives the projection 131 for movement therein. -As the pressing member 5 rotates from the first rotary position (See FIG. 2) to the second rotary position (See FIG. 4),

MARKED SPECIFICATION

F-8660

Ser. No.

the projection 131 ~~relatively moves~~moves relative to and within the recess 132 and comes into contact with the inside surface of the recess 132, resulting in prevention of further travel of the projection 131. ~~In the illustrated~~

~~embodiment, the~~The projection 131 is disposed in the body 4, and the recess

5 132 is disposed in the pressing member 5.- Actually, when the recess 132 moves, and the inside surface of the recess 132 comes into contact with the projection 131, the movement of the recess 132, in other words, the rotation of the pressing member 5, is prevented.

The interlock means 140 ~~serves to cause~~causes the pressing member 5 in 10 the second rotary position to move between the press releasing position and the pressing position ~~as interlocked and~~interlocks with the rotation of the rotary member 6 between the middle rotary position (See FIGs. 4 and 5) and the other rotary position (See FIGs. 6 to 9). -Specifically, the interlock means 140

includes: a guide means 150 for axially guiding the rotary member 6 by rotating

15 the rotary member 6, ~~to move in the same direction as the direction of the axis~~

7, and a support means 160 for supporting the pressing member 5 so that it

moves between the press releasing position and the pressing position along with

the axial movement of the rotary member 6 ~~in the same direction as the~~

~~direction of the axis 7~~. - Thus, the rotary member 6, as it rotates between the

20 middle rotary position and the other rotary position, is guided to ~~move in the~~

MARKED SPECIFICATION

F-8660

Ser. No.

~~same direction as the direction of the axis 7~~axially translate.- Along with this movement, the pressing member 5 supported by the support means 160 moves between the press releasing position on the press releasing side and the pressing position on the pressing side. -Here, the guide means 150 includes: a guided
5 projection 151 provided in one of the body 4 and the rotary member 6, and a first guide surface 152 ~~serving as a guide surface~~ provided in the other of the body 4 and the rotary member 6, for ~~relatively~~ guiding the guided projection 151 relative to the first guide surface 152.- In other words, as the guided projection 151 is ~~relatively guided by~~guided relative to and with the first guide
10 surface 152, the rotary member 6 is guided to ~~move in the same direction as the direction of the axis 7.~~ axially translate.

_____The support means 160 includes: the coil spring 8 serving as a resilient element for urging the pressing member 5 toward the press releasing position from the pressing position; and a receiving portion 6c that is provided on the
15 rotary member 6 to receive the pressing member 5 against the urging force of the coil spring 8 as a resilient element. -Thus, as the rotary member 6 rotates between the middle rotary position and the other rotary position and is guided by the guide means 150 to ~~move in the same direction as the direction of~~translate, along with the ~~axis 7~~axial movement, the pressing member 5 urged
20 by the coil spring 8 ~~serving as a resilient element,~~ and is received by the

MARKED SPECIFICATION

F-8660

Ser. No.

receiving portion 6c of the rotary member 6 ~~moves~~ and axially translates
between the press releasing position and the pressing position ~~along with the~~
~~movement in the same direction as the direction of the axis 7. In the illustrated~~
~~embodiment, the~~ The guided projection 151 is disposed in the rotary member 6,
5 and the first guide surface 152 is disposed in the body 4.

Specifically, the body 4 includes: a plate-like base portion 4b, and a
cylindrical portion 4c projected upward from the central portion of the base
portion 4b. -Here, the base portion 4b has attachment holes 4d ~~and 4d~~ for
attachment bolts ~~11 and~~ 11 to pass through for securing the body 4 to the
10 fixingsupport base 1.- The cylindrical portion 4c has a base portion in which a
step 4e of a greater diameter is formed.- The inside of the cylindrical portion 4c
constitutes the axial bore 4a and passes through the cylindrical portion 4c and
the base portion 4b. -To the fore-end of the cylindrical portion 4c is mounted a
pin 4f with its base end side embedded. -The projecting tip of the pin 4f serves
15 as the projection 131; which ~~constitutes~~ is the rotary range restricting means
130.

The cylindrical portion 4c is formed with a first elongate slot 4g and a
second elongate slot 4h continuously connected with each other (See FIG. 1).
The inside peripheral surface of the first elongate slot 4g serves as the first
20 guide surface 152 for ~~relatively~~ guiding the guided projection 151 of the rotary

MARKED SPECIFICATION

F-8660

Ser. No.

member 6 relative to the first guide surface 152 when the rotary member 6 rotates between the middle rotary position and the other rotary position. —

_____The inside peripheral surface of the second elongate slot 4h serves as the second guide surface 171 for ~~relatively~~ guiding the guided projection 151

5 relative to the second guide surface 171 when the rotary member 6 rotates between the one rotary position and the middle rotary position. ~~By the~~The guided projection 151, the second guide surface 171, the holding means 120 and the contact means 110, together guide the pressing member 5 ~~positioned, while~~

being in the press releasing position ~~and, from the side distant from the pressing position is guided to move~~ to the side near the pressing position ~~along with its~~

10 rotation as the pressing member 5 rotates from the first rotary position (See

FIGs. 2 and 3) to the second rotary position (See FIGs. 4 and 5). -The coil

spring 8 is fitted over the cylindrical portion 4c of the body 4. ~~Besides~~In addition, an outer cylinder 10 is fitted over the coil spring 8.- One end face of

15 the coil spring 8 is in contact with the step 4e of the body 4 while the other end face is in contact with a raised step 10a formed on the inside surface of the outer cylinder 10.

- The rotary member 6 includes the shank portion 6a inserted in the axial bore 4a of the body 4 so as to be rotatable about and slidable along the axis 7,
20 and the receiving portion 6c located on the fore-end side of the shank portion

MARKED SPECIFICATION

F-8660

Ser. No.

6a. -The shank portion 6a and the receiving portion 6c are joined as a single member with a bolt 6d as a securing member. -A guide pin 6e is inserted in the shank portion 6a and secured with a set screw 6f.- The projecting fore-end of the guide pin 6e is the guided projection 151 constituting the guide means 150.-

5 _____The receiving portion 6c has a disk like shape with its circumferential surface provided with a detachable operation handle 6g for manual rotation. -A surface (the underside ~~in the illustrated embodiment~~) of the receiving portion 6c facing the pressing member 5 is the second sliding surface 6b.- The receiving portion 6c is provided with the plunger 9 as embedded therein, with the
10 pressing piece 9a resiliently urged to project outside and recede inside the second sliding surface 6b.

 The pressing member 5 has the shape of a horizontally elongated plate and the through-hole 5a is formed at one side thereof to pass through. ~~Since~~As the shank portion 6a of the rotary member 6 is inserted in the through-hole 5a,
15 the pressing member 5 is allowed to rotate about and slide along the axis 7. -A surface (the upside ~~in the illustrated embodiment~~) of the pressing member 5 that faces the receiving portion 6c of the rotary member 6 is the first sliding surface 5b. -To the other side of the pressing member 5 is attached using a bolt 5d, a fitting 5c for pressing the workpiece 2.- The recess 132, constituting the rotary
20 range restricting means 130, is formed along the circumference of the

MARKED SPECIFICATION

F-8660

Ser. No.

through-hole 5a in the pressing member 5. -The recess 132,~~in the illustrated embodiment,~~ opens to the through-hole 5a side and the bottom side.

While respective FIGs. 6 to 7, and FIGs. 8 to 9 show a state in which the rotary member 6 is in the other rotary position and the pressing member 5 is in the second rotary position and pressing position, FIGs. 6 and 7 show a target position, calculated from design, where the workpiece 2 is to be pressed.- FIGs. 8 and 9 show the rotary member 6 and the pressing member 5 having advanced furthermore from the target position, with the rotary member 6 in the maximum rotary position and the pressing member 5 in the maximum pressing position.

FIGs. 10 and 11 show an example of clamping the workpiece 2 to a fixture base 1a~~constituting the fixing base 1,~~ using four sets of the clamp device 3.- FIG. 10 is a perspective view, showing a state in which the workpiece 2 is not yet placed or has been removed. -FIG. 11 is a perspective view, showing a state in which the workpiece 2 is clamped.- In the drawings, reference numeral 1b denotes supporters which are mounted on the fixture base 1a to support the workpiece 2.- Reference numeral 1c denotes spacers which are likewise mounted on the fixture base 1a for the clamp devices 3 to be secured to, respectively. -Thus, the fixingsupport base 1 of the embodiment shown in FIGs. 10 and 11 includes the supporters 1b~~and 1b,~~ and spacers 1c₁ and ~~1c,~~ in addition to the fixture base 1a.

MARKED SPECIFICATION

F-8660

Ser. No.

Functional effects of the clamp device 3 constituted as above are described below.- With the clamp device 3, when the rotary member 6 is rotated from the one rotary position (See FIGs. 2 and 3) to the middle rotary position (See FIGs. 4 and 5), the pressing member 5, while being held in the press releasing position by the holding means 120, is rotated by the contact means 110 from the first rotary position to the second rotary position, as the rotary member 6 rotates. -When the rotary member 6 is rotated further from the middle rotary position (See FIGs. 4 and 5) to the other rotary position (See FIGs. 6 to 9), the pressing member 5, while ~~being remained~~remaining in the second rotary position by the rotary range restricting means 130, is moved by the interlock means 140 from the press releasing position to the pressing position and presses the workpiece 2.

In other words, in order to clamp the workpiece 2 to the fixingsupport base 1, first the workpiece 2 is placed in the clamping position and the rotary member 6 is then rotated from one rotary position past the middle rotary position to the other rotary position.- This causes the pressing member 5 to rotate from the first rotary position (See FIGs. 2 and 3) not facing the workpiece 2 to the second rotary position (See FIGs. 4 and 5) facing the workpiece 2 as the rotary member 6 rotates up to the middle rotary position. By the rotation of the rotary member 6 up to the other rotary position, the

MARKED SPECIFICATION

F-8660

Ser. No.

pressing member 5, while ~~being remained~~remaining in the second rotary position, moves from the press releasing position (See FIG. 5) on the press releasing side to the pressing position (See FIGs. 7 and 9) on the pressing side to press the workpiece 2. -Thus, the workpiece 2 is clamped to the

5 fixingsupport base 1.

- In contrast, if the rotary member 6 is rotated from the other rotary position to the one rotary position side, then the pressing member 5 is moved by the interlock means 140 from the pressing position to the press releasing position side, and as the rotary member 6 rotates, the pressing member 5 is

10 rotated by the contact means 110 from the second rotary position to the first rotary position. -In other words, if the workpiece 2 is to be removed from the fixingsupport base 1, the rotary member 6 is rotated from the other rotary position to the one rotary position.- This causes the pressing member 5 to move from the pressing position to the press releasing position side, and to rotate

15 from the second rotary position facing the workpiece 2 to the first rotary position not facing the workpiece 2. -Here, the workpiece 2 is removed from the fixingsupport base 1.

- With the clamp device 3 as described above, if the workpiece 2 is to be placed on and clamped to the fixingsupport base 1 or if the workpiece 2 is to be

20 removed from the fixingsupport base 1, because rotating the rotary member 6

MARKED SPECIFICATION

F-8660

Ser. No.

causes the pressing member 5 to rotate between the first rotary position not facing the workpiece 2 and the second rotary position facing the workpiece 2, and to move between the press releasing position on the press releasing side and the pressing position on the pressing side, the workpiece 2 is easily clamped to
5 or removed from the ~~fixing~~support base 1.

As for the contact means 110, because the first sliding surface 5b and the second sliding surface 6b of the pressing member 5 and the rotary member 6 facing each other are urged by the coil spring 8 ~~as a resilient member~~ to tightly contact each other, the pressing member 5 securely rotates between the first
10 rotary position and the second rotary position as the rotary member 6 rotates. ~~Besides~~In addition, owing to the engagement of the resiliently urged pressing piece 9a (engagement portion 112) of the rotary member 6 with the engagement recess 111 of the pressing member 5, the pressing member 5 and the rotary member 6 are prevented from rotating ~~relatively~~relative to each other.—

15 _____ Therefore, the pressing member 5 rotates more certainly between the first rotary position and the second rotary position as the rotary member 6 rotates.- In other words, while the rotary member 6 is being rotated from one rotary position to the middle rotary position, the pressing piece 9a is in engagement with the engagement recess 111, so that the rotary member 6 and
20 the pressing member 5 rotate together.- Rotating the rotary member 6 from the

MARKED SPECIFICATION

F-8660

Ser. No.

middle rotary position to the other rotary position causes slippage between the first sliding surface 5b and the second sliding surface 6c, and also disengagement between the engagement recess 111 and the pressing piece 9a.-

In contrast, if the rotary member 6 is rotated from the other rotary position to the one rotary position, the pressing piece 9a engages the engagement recess 111 in the middle of the rotation.

With the press releasing position of the pressing member 5 having a range, that is, a height difference, due to relationship between the second guide surface 171 (the second elongate slot 4h) and the guided projection 151 (the guide pin 6e), when the pressing member 5 rotates from the first rotary position to the second rotary position, the pressing member 5 ~~is adapted to move~~moves from the side distant from the pressing position to the side near the pressing position.—

It is therefore possible to rotate the pressing member 5 apart from the workpiece 2 in the ~~same~~axis 7 direction ~~as the direction of the axis 7~~, that is, the up-and-down direction so that the pressing member 5 can pass an obstacle, if any, ~~on the way~~while the pressing member 5 moves from the first rotary position to the second rotary position. ~~Besides~~In addition, because the pressing member 5 approaches the pressing position while it rotates from the first rotary position to the second rotary position, it is possible to reduce the stroke between

MARKED SPECIFICATION

F-8660

Ser. No.

the press releasing position and the pressing position in the second rotary position. -Therefore, it is possible to increase the pressing force with which the pressing member 5 presses the workpiece 2. -In particular in the embodiment shown in FIG. 1, because the gradient of the first guide surface 152 (the first elongate slot 4g) is ~~gentler~~smaller than the second guide surface 171 (the second elongate slot 4h), it is possible to further increase the force for pressing the workpiece 2.

- Incidentally, the invention is not limited to the above embodiment but may be modified in various ways. -For example, the ~~fixing~~support base 1 may be any table such as an MC pallet, machine table, etc., other than the fixture base 1a.- The object to be clamped may be for example a jig, a fixture, die or the like, other than the workpiece 2.

- The contact means 110 in the clamp device 3 includes: the coil spring 8 serving as a resilient member, the engagement recess 111, and the plunger 9 serving as the engagement member 113. -However, the engagement recess 111 and the plunger 9 may not be used.

- The body 4 has the plate-like base portion 4b for attachment to the ~~fixing~~support base 1.- Alternatively, as shown in FIG. 12, the body 4 may include: a tool engagement portion 181 to be engaged with a tool such as a

MARKED SPECIFICATION

F-8660

Ser. No.

wrench; a first thread portion 183 to be engaged with a nut 182; and a second thread portion 184 to be screwed in the fixingsupport base 1, in vertical order.

- The rotary member 6 may not have the operation handle 6g for rotary operation.- Alternatively, a tool engagement portion 191 for engaging a tool 190
5 such as a wrench may be provided, as shown in FIG. 13.

- The rotary range restricting means 130 may not include the projection 131 disposed in the body 4 and the recess 132 disposed in the pressing member 5, but, as shown in FIGs. 14 and 15, may include: a recess 132 as a cut out formed at the top end of an outer cylinder 201 that is fixed to the body 4, and a
10 projection 131 extending sideways from the through-hole 5a side of the pressing member 5. -In other words, the rotary range restricting means 130 may include the recess 132 on the body 4 side and the projection 131 on the pressing member 5 side.

- The clamp device 3 includes the coil spring 8 disposed to urge between
15 the body 4 and the pressing member 5.- Alternatively, the coil spring 8 may be replaced, as shown in FIG. 16, with a resilient piece 301, which is disposed to urge between the rotary member 6 and the pressing member 5 and serves as a resilient member which constitutes at least the contact means 110, such as a coned disk spring and a spring washer. ~~In the illustrated embodiment, the~~The
20 resilient piece 301 serves as a resilient body as an element constituting the

MARKED SPECIFICATION

F-8660

Ser. No.

holding means 120, and also serves as a resilient element as an element constituting the support means 160.- Incidentally, in FIG. 16, the projection 131 of the rotary range restricting means 130 is disposed in the pressing member 5, and the recess 132 is disposed in the body 4.

5 _ As for the guide means 150, the guided projection 151 is disposed in the rotary member 6, and the guide surfaces 152, 171 are in the body 4.-

Alternatively, they may be disposed contrarily, with the guided projection 151 disposed in the body 4, and with the guide surfaces 152, 171 in the rotary member 6.

10 _ In the contact means 110, while the engagement recess 111 is disposed in the pressing member 5 and the plunger 9 serving as the engagement member 113 is disposed in the rotary member 6, they may be disposed contrarily, with the engagement recess 111 disposed in the rotary member 6 and with the plunger 9 in the pressing member 5.

15 ~~INDUSTRIAL APPLICABILITY~~

_ As described above, the clamp device according to the invention may be used to clamp workpieces, jigs, fixtures, or dies to a fixture base, MC pallet, machine table, for example.-

20 The present invention may be embodied in other specific forms without departing from its spirit or essential characteristics. The described embodiments

MARKED SPECIFICATION

F-8660

Ser. No.

are to be considered in all respects only as illustrative and not as restrictive.

The scope of the invention is, therefore, indicated by the appended claims and their combination in whole or in part rather than by the foregoing description.

All changes that come within the meaning and range of equivalency of the

5 claims are to be embraced within their scope.

ABSTRACT OF THE DISCLOSURE

To provide a clamp device capable of simply clamping an object to be
~~clamped to~~ and removing it from a ~~fixingsupport~~ base.- In the clamp device-3, a
body-4, a pressing member-5 for pressing a workpiece-2, and a rotary member
5 6 are allowed to rotate ~~relatively~~relative to each other.- The pressing member 5
~~is adapted to rotate~~rotates between a first rotary position not facing the
workpiece 2-and a second rotary position facing the workpiece-2.- In the second
rotary position, the pressing member-5 is also movable between a press
releasing position and a pressing position. -Here, when the rotary member-6 is
10 rotated from one rotary position to a middle rotary position, the pressing
member-5, while being held in the ~~process~~press releasing position by a holding
means-120, is rotated by a contact means-110 from the first rotary position to
the second rotary position as the rotary member 6-rotates.- Next, when the
rotary member 6-is rotated to ~~the other~~another rotary position, the pressing
15 member-5, while ~~being remained~~remaining in the second rotary position by the
rotary range restricting means-130, is moved to the pressing position by an
interlock means-140.